

Premium Acrylic Paint 9000



PHYSICAL PROPERTIES :

Premium paint is a high grade Acrylic paint formulated for maximum coverage at an economical cost over concrete or stucco. It is formulated to cover in one application at approximately 0.5 gal per sq.ft. This formula is made to cover and adhere to a slightly chalky surface.

SPECIFICATIONS IN PACKAGES

| | |
|-------------------------------|-----------|
| Non-Volatile Liquid Elastomer | 26% |
| % Pigments | 37% |
| % Solvents | 37% |
| Container Stability | 12 months |

TYPICAL PROPERTIES OF CURED COATINGS

| | |
|-----------------------------------------|--------------|
| Flash Point | None |
| Dry Time at 77°F | |
| To Touch | 3 hours |
| Throughout, Days | 1 day |
| Film Thickness of 1 gal/100 square feet | 8 mils |
| Color Stability | Excellent |
| Temperature Range | |
| Application Degree F | 50 - 120°F |
| Service Degree F. | -10 - 180°F |
| Resistance to: | |
| Oil | Good |
| Sunlight | Excellent |
| Chemicals | Excellent |
| Ozone | Excellent |
| Permeability, Water Vapor ASTM E-96 | 5 U.S. Perms |
| Weathering Effect | Excellent |
| Adhesion: Urethane Foam | Good |
| Concrete, stucco | Excellent |
| Wood | Excellent |
| Cold Temperature Flexibility | Good |
| Abrasion Resistance | Good |
| Resistance, Foot Traffic | Fair |

9000